

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
16 June 2005 (16.06.2005)

PCT

(10) International Publication Number
WO 2005/054587 A1

(51) International Patent Classification⁷: E02D 7/22, 5/56

CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:

PCT/CA2004/002064

(22) International Filing Date: 1 December 2004 (01.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2,452,448 4 December 2003 (04.12.2003) CA

(71) Applicant and

(72) Inventor: NIMENS, Joseph, R.E. [CA/CA]; 172A Rocky Shore Road, Callander, Ontario P0H 1H0 (CA).

(74) Agent: EVERITT, Peter, R.; Kvas Miler Everitt, 3300 Bloor Street West, Suite 3100, Toronto, Ontario M8X 2X3 (CA).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR INSTALLING A HELICAL PILE



(57) Abstract: An apparatus and a method to assist in the installation of a helical pile. The apparatus comprises a drive mechanism having an engaged and a disengaged configuration. When in its engaged configuration the drive mechanism operatively grasps the exterior surface of the helical pile. When in its disengaged configuration the drive mechanism operatively releases the exterior surface of the helical pile. Movement of the drive mechanism when in its engaged configuration causes rotational movement of the pile. When in its disengaged configuration the drive mechanism moves without rotation of the pile.

WO 2005/054587 A1